

CMI165

Copper Thickness Measurement with Temperature Compensation



Oxford Instruments **CMI165** provides unique temperature compensated Copper thickness measurements in an ergonomic hand-held device. Measurements on Copper are affected by the temperature of the sample. The **CMI165** accounts for temperature in the measurement of thickness ensuring accurate in-process inspection results regardless of Copper temperature. This versatile, portable gauge equipped with protective case, has a rugged and durable design that allows it to be taken into the harshest environments.



- Measure hot or cold Cu on PCBs
- Reduce waste by eliminating the need for coupons
- Measure foil or laminated Cu thickness in μm , mils or oz
- Sort Cu by weight at incoming inspection, before drilling, shearing or plating
- Quantify Cu thickness after etching or planarizing
- Verify Cu plating thickness on PCB surfaces

The Business of Science[®]



Proprietary SRP-T1 measurement probe



User Interface available in both English and Simplified Chinese

- SRP-T1 Replaceable Probe Tip – no recalibration necessary
- Spare SRP-T1 ensures no factory downtime
- Illuminated probe tip for easy positioning on copper traces

Specifications:

- Copper thickness is measured using 4-point probe electrical resistance method and conforms to standard EN 14571.
- Thickness measurement ranges
 - Copper Electroless: (0.25-12.7) μm , (0.01-0.5) mils
 - Copper Electrodeposited: (2.0-254) μm , (0.1-10) mils
- High repeatability and reliability: $\sigma \approx 0.08 \mu\text{m}$ at 20 μm (0.003 mils at 0.79 mils)
- Statistical analysis includes data recording, average, standard deviation and high-low reporting
- Measurement units in μm , mils or oz
- User interface in English or Simplified Chinese
- Measure etched traces without line width standards
- Store 9,690 measurements (with optional date and time stamp)

- USB 2.0 high-speed data transfer interfaced with Microsoft Excel™
- Factory calibrated and certified
- Customizable for other applications
- Static or continuous mode measurement
- Powered by regular AA batteries



Oxford Instruments, at High Wycombe, UK, operates Quality Management Systems approved to the requirements of BS EN ISO 9001. This publication is the copyright of Oxford Instruments Analytical Limited and provides outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. Oxford Instruments' policy is one of continued improvement. The company reserves the right to alter, without notice, the specification, design or conditions of supply of any product or service. Oxford Instruments acknowledges all trade marks and registrations.

© Oxford Instruments Analytical Ltd, 2008. All rights reserved.

Part no: OIIA/046/A/0108



Certificate No FM29142

