

Back Up Board RYM-W



Description

Alltech RYM-W is a birch & oak free, sanded, melamine paper laminated, high density Back Up Board, that is made for the use of drilling high TG multilayers and/or micro via's. It allows increased stack highs and reduces exit burrs due to high density core and laminated melamine-paper on top. The main difference in production is the pressing process. The use of special resins and binders, as well as laminating in a continuous process reduces internal stress, being beneficial to flatness. Alltech RYM-W offers very good drill properties, an excellent price / performance ratio and meets nowadays technical and economic requirements.

Technical Data

Physical Property	Reported Units	Typical Values
Thickness	mm	2.6 ± 0.15
Size Tolerance	mm	± 2.0
Squareness	mm/m	≤ 2.0
Straightness	mm/m	≤ 2.0
Warpage	mm/m	≤ 5.0
Density	kg/m ³	1000 ± 50
Surface Hardness	HD	85 ± 5
Surface	Color	White
Internal Bond	MPa	≥ 1.8
Modulus of Elasticity	%	≥ 4000
Moisture Content	%	4~8



Surface

Alltech RYM-W is available in white

Form of Delivery / Tooling

Alltech RYM-W is available in sheets, panels, toolled or un-tooled according to customer demand.

Quality

CCI and supplier are certified according to ISO:9001.

Storage

Materials are not allowed to be stored in open storage or in storage areas exposed to moisture. Increased humidity can cause the materials to warp. Store the materials in a dry, well-ventilated indoor area. Place on a flat surface or shelf and keep away from sources of fire. Storage temperature: 5–25 °C, relative humidity: < 60%

Environment / Disposal

Alltech RYM-W is FSC compliant, hazard-free and non-toxic. Disposal of wastes can take place by consumer according to local environmental and disposal regulations.

General Safety Information

Only use the product for applications described in the product data sheet, the product is intended for industrial use only, the product is not suitable for food industry, the product must not be eaten.